

# LTK-TC6040 CNC LATHE <<<<

Fanuc Oi TF Controller  
Hydraulic Chuck  
Gang Tool  
Frequency Spindle  
Screws, Bearings, Lubrication (China)  
Taiwan Guideway  
Chain type chip conveyor



SCAN WITH YOUR CELL PHONE  
Parque Tecnológico Innovación, Querétaro, C.P. 76246  
E-mail: [latinatek@latinatek.com.mx](mailto:latinatek@latinatek.com.mx) / [www.latinatek.com.mx](http://www.latinatek.com.mx)  
442-221-6200 / 442-221-6333



## Main characteristics

Unique design of robust structure and high precision. Linear guides for smoother and more precise movements. Compact and symmetrical spindle with thermal stability.

| SPECIFICATION                         | TC6040                  |
|---------------------------------------|-------------------------|
| <b>Bed incline</b>                    | 60°                     |
| <b>Cutting length</b>                 | 300 mm                  |
| <b>Cutting capacity over bed</b>      | Ø200 mm                 |
| <b>Cutting capacity over support</b>  | Ø450 mm                 |
| <b>Chuck size</b>                     | A2-5                    |
| <b>Spindle power</b>                  | 5.5 Kw                  |
| <b>Spindle speed</b>                  | 4000 rpm                |
| <b>Spindle bore</b>                   | Ø58 mm                  |
| <b>Through-spindle Draw tube bore</b> | Ø55 mm                  |
| <b>Rapid feed</b>                     | 20 m/min                |
| <b>X Axis Travel</b>                  | 400 mm                  |
| <b>Z Axis Travel</b>                  | 3000 mm                 |
| <b>Positioning accuracy</b>           | ±0.008(X); ±0.011(Z) mm |
| <b>Repeatability accuracy</b>         | ±0.003(X); ±0.005(Z) mm |
| <b>Overall dimension</b>              | 3200 x 1950 x 2000 mm   |
| <b>Weight</b>                         | 4100 Kg                 |